

Straight connection joint



Straight cast resin cable joints are suitable for plastic and paper insulated LV cables. These joints are suitable for use in power, telecoms and signalisation. The joints are approved in accordance with the standard DIN EN 50393 (VDE 0278-393):2006-11
Designed for UK armoured cables to allow plenty of room to work.

Features

- Type tested according to: EN 50393:2006-11
- Hydrolysis resistant polyurethane resin in a transparent 2 component bag
- Strong transparent shells
- Fully waterproof, no resin leakage
- Cable spacers included
- Complete kit, sealing tape, sandpaper, and protective gloves also included
- Installation instructions with clear drawings
- Quick and easy installation
- Connectors and earthing kits available on request
- Other shell size dimensions available on request

Straight connection joint

Specifications

Armoured

Size of conductor	1 core Armoured	2 core Armoured	3 core Armoured	4 core Armoured	5 core Armoured
1.5mm ²	N/A	ST 6	ST 6	ST 6	ST 6*
2.5mm ²	N/A	ST 6	ST 6	ST 6	ST 6*
4mm ²	N/A	ST 6	ST 6	ST 6	ST 6*
6mm ²	N/A	ST 6	ST 6	ST 6	ST 16*
10mm ²	N/A	ST 16*	ST 16	ST 16	ST 35/70*
16mm ²	N/A	ST 16	ST 16	ST 16	ST 35/70*
25mm ²	N/A	ST 16*	ST 35/70	ST 35/70	ST 35/70*
35mm ²	N/A	ST 35/70*	ST 35/70	ST 35/70	ST 35/70*
50mm ²	ST 16*	ST 35/70*	ST 35/70	ST 35/70	ST 95*
70mm ²	ST16*	ST 35/70*	ST 35/70	ST 35/70	ST 95*
95mm ²	ST 35/70*	ST 35/70*	ST 95	ST 95	ST 120*
120mm ²	ST 35/70*	ST 95*	ST 95	ST 120	ST 300*
150mm ²	ST 35/70*	ST 95*	ST 120	ST 185	ST 400*
185mm ²	ST 95*	ST 120*	ST 185	ST 185	ST 400*
240mm ²	ST 95*	ST 120*	ST 300	ST 300	ST 400*
300mm ²	ST 120*	ST 185*	ST 300	ST 300	ST 400*
400mm ²	ST 300*	ST 300*	ST 400	ST 400	ST 400*

* Denotes: Not a standard joint

Straight connection joint

Un-armoured

Size of conductor	1 core Un-armoured	2 core Un-armoured	3 core Un-armoured	4 core Un-armoured	5 core Un-armoured
1.5mm ²	N/A	ST 6	ST 6	ST 6	ST 6*
2.5mm ²	N/A	ST 6	ST 6	ST 6	ST 6*
4mm ²	N/A	ST 6	ST 6	ST 6	ST 6*
6mm ²	N/A	ST 6	ST 6	ST 6	ST 6*
10mm ²	N/A	ST 6*	ST 6*	ST 6*	ST 6*
16mm ²	N/A	ST 6*	ST 6*	ST 6*	ST 16*
25mm ²	N/A	ST 6*	ST 6*	ST 6*	ST 16*
35mm ²	N/A	ST 16*	ST 16*	ST 35/70	ST 35/70*
50mm ²	ST 16*	ST 16*	ST 35/70	ST 35/70	ST 35/70*
70mm ²	ST 16*	ST 16*	ST 35/70	ST 35/70	ST 35/70*
95mm ²	ST 35/70*	ST 35/70*	ST 35/70*	ST 35/70*	ST 95*
120mm ²	ST 35/70*	ST 35/70*	ST 35/70*	ST 35/70*	ST 95*
150mm ²	ST 35/70*	ST 35/70*	ST 95*	ST 95*	ST 95*
185mm ²	ST 35/70*	ST 95*	ST 95*	ST 95*	ST 120*
240mm ²	ST 35/70*	ST 95*	ST 120*	ST 120*	ST 185*
300mm ²	ST 35/70*	ST 95*	ST 120*	ST 185*	ST 300*
400mm ²	ST 95*	ST 120*	ST 185*	ST 185*	ST 300*

* Denotes: Not a standard joint

Straight connection joint

Products

Art.nr.	Product Name	Cable Diameter (mm)	Dimensions (mm)	Order unit
CM0	Straight connection joint telecom and Signalisation	Ø 05 - 20	L200 x Ø35	per piece
CM1	Straight connection joint telecom and Signalisation	Ø 08 - 30	L250 x Ø45	per piece
CM2	Straight connection joint telecom and Signalisation	Ø 10 - 34	L320 x Ø60	per piece
CM2.5	Straight connection joint telecom and Signalisation	Ø 26 - 53	L355 x Ø72	per piece
CM3	Straight connection joint	Ø 30 - 48	L450 x Ø75	per piece
CM4	Straight connection joint	Ø 37 - 67	L547 x Ø108	per piece
CM5	Straight connection joint	Ø 62 - 68	L700 x Ø140	per piece
CM6	Straight connection joint	Ø 45 - 70	L800 x Ø160	per piece
CM7	Straight connection joint	Ø 70 - 105	L1345 x Ø155	per piece