


# LLX T5



LLX228ALDP

## Surface mounted light fittings for T5 lamps

### Body:

White painted (RAL 9003) metal sheet

### Optic (&):

ALDP - double parabolic louvre category C2 of highly polished aluminium

MATDP - double parabolic louvre category C2 of mat aluminium

AL - parabolic louvre of highly polished aluminium with mat aluminium cross blades

B - white parabolic louvre

### Wiring (#):

EP - high frequency ballast HFB (standard)

EPSA - HFB analogue dimmable (1-10 V)

EPSD - HFB digital dimmable TRIDONIC ECO

EPSSD - HFB digital dimmable DALI

MULTIWATT - universal HFB for T5 lamps

### Application:

These light fittings can be used as surface mounted or suspended.

### Accessories:

Tube suspension

Cord suspension ZH22

Protection grid OM

### Versions (@):

NZ - emergency pack

OK - double-circuit wiring

RAL9006 - surface finished in RAL 9006

### Note:

Surface mounted style of installation is recommended. When light fittings are suspended, they should be hung by 4 cords or tubes.

	W	A	B	X	Y	kg
LLX114 (24) &#@	1x14 (24)	610	153	300	-	1,7
LLX214 (24) &#@	2x14 (24)	610	238	300	150	2,6
LLX414 (24) &#@	4x14 (24)	610	410	300	330	3,4
LLX128 (54) &#@	1x28 (54)	1210	153	900	-	3,0
LLX228 (54) &#@	2x28 (54)	1210	238	900	150	4,0
LLX328 (54) &#@	3x28(54)	1210	324	900	235	5,0
LLX135 (49, 80) &#@	1x35 (49, 80)	1510	153	1200	-	4,0
LLX235 (49, 80) &#@	2x35 (49, 80)	1510	238	1200	150	5,5

